

RH-Temp **Portable** Data Logger

Features:

- Memory for 32,700 readings
- LCD to show logging information easily
- Free selectable measurement cycle from 1sec to 24hrs.
- Battery life: more than 3 years (Under Ideal condition at 22oC)
- Display all status for Alarm and Record through 2 LED's.
- Alarm display if user-defined max/min values are exceeded
- Analysis software used to view graphically or Text mode for logging data.
- USB Computer Interface
- (Advanced Software Program for all windows)



easy Log

Technical Data :

Basic Functions	RH		Temp.			
	Measuring Range	0 ~ 100%RH		-40° ~ 70°C		-40° ~ 158°F
Accuracy	0 ~ 35% & 80 ~ 100% RH	±5% RH	-40 ~ 40°C	±1.0°C	-40 ~ 104°F	±1.8 °F
	35% ~ 80% RH	±3% RH	40 ~ 70°C	±2.0°C	104 ~ 158°F	±3.6 °F
Resolution	0.1%RH		0.1°C			
Memory	32,000 (16,000each for temperature and Humidity)					
Measuring Rate	1sec. to 24hrs					
Response Time	< 30 S					

Special Function :

Memory	32700 readings	Power Supply	3.6V Lithium Battery
--------	----------------	--------------	----------------------

- Standard Accessory : Battery, Holding Case, Safety Lock
USB Cable with Software
- Dimensions : 94.8(H) * 51.4(W) * 29.5(D) MM